

RECEIVED  
CENTRAL FAX CENTERAPPLICANT(S): GORDON, Mcir  
SERIAL NO.: 10/734,122  
FILED: December 15, 2003  
Page 2

JUN 25 2007

## AMENDMENTS TO THE CLAIMS

Please add or amend the claims to read as follows and cancel without prejudice the claims marked as cancelled:

1- 8 (Cancelled)

9. (Currently Amended) A combiner comprising:

a circuit comprising a first group of six reactive elements to couple two differential input ports to two differential output ports in a first manner;

a second group of two reactive elements to couple one of said two differential input ports to one of said two differential output ports in a second, different manner; and

a third group of four reactive elements, each to couple a positive terminal and a negative terminal of a respective one of said two differential input ports and said two differential output ports; wherein reactive elements of said first group and said second group have substantially equivalent inductive impedances and reactive elements of said third group have substantially equivalent capacitive impedances.

10. (Original) The apparatus of claim 9, wherein said first manner is to couple positive terminals to positive terminals and to couple negative terminals to negative terminals, and said second manner is to couple positive terminals to negative terminals.

11. (Original) The apparatus of claim 9, wherein said first manner is to couple positive terminals to negative terminals, and said second manner is to couple positive terminals to positive terminals and to couple negative terminals to negative terminals.

12. (Original) The apparatus of claim 9, wherein at least one of said reactive elements is a discrete component.

13. (Cancelled)

14. (Original) The apparatus of claim 9, wherein reactive elements of said first group and said second group have substantially equivalent capacitive impedances and reactive elements of said third group have substantially equivalent inductive impedances.

APPLICANT(S): GORDON, Meir  
SERIAL NO.: 10/734,122  
FILED: December 15, 2003  
Page 3

RECEIVED  
CENTRAL FAX CENTER  
JUN 25 2007

15. (Original) The apparatus of claim 14, further comprising:  
a supply coupled to center taps of said reactive elements of said third group.
16. (Original) The apparatus of claim 14, further comprising:  
a supply return coupled to center taps of said reactive elements of said third group.
- 17-19. (Cancelled)
20. (Original) A communication device comprising:  
a dipole antenna;  
a power amplifier coupled to said dipole antenna; and  
a combiner coupled to said power amplifier, wherein said combiner includes at least:  
a first group of six reactive elements to couple two differential input ports to two differential output ports in a first manner;  
a second group of two reactive elements to couple one of said two differential input ports to one of said two differential output ports in a second, different manner; and  
a third group of four reactive elements, each to couple a positive terminal and a negative terminal of a respective one of said two differential input ports and said two differential output ports.
21. (Original) The communication device of claim 20, wherein said first manner is to couple positive terminals to positive terminals and to couple negative terminals to negative terminals, and said second manner is to couple positive terminals to negative terminals.
22. (Original) The communication device of claim 20, wherein said first manner is to couple positive terminals to negative terminals, and said second manner is to couple positive terminals to positive terminals and to couple negative terminals to negative terminals.
23. (Original) The communication device of claim 20, wherein reactive elements of said first group and said second group have substantially equivalent inductive impedances and reactive elements of said third group have substantially equivalent capacitive impedances.

RECEIVED  
CENTRAL FAX CENTER  
JUN 25 2007

APPLICANT(S): GORDON, Meir  
SERIAL NO.: 10/734,122  
FILED: December 15, 2003  
Page 4

24. (Original) The communication device of claim 20, wherein reactive elements of said first group and said second group have substantially equivalent capacitive impedances and reactive elements of said third group have substantially equivalent inductive impedances.

25. (Original) A communication system comprising:

a first communication device; and

a second communication device, said second communication device including at least:

a combiner including at least:

a first group of six reactive elements to couple two differential input ports to two differential output ports in a first manner;

a second group of two reactive elements to couple one of said two differential input ports to one of said two differential output ports in a second, different manner; and

a third group of four reactive elements, each to couple a positive terminal and a negative terminal of a respective one of said two differential input ports and said two differential output ports.

26. (Original) The communication device of claim 25, wherein said first manner is to couple positive terminals to positive terminals and to couple negative terminals to negative terminals, and said second manner is to couple positive terminals to negative terminals.

27. (Original) The communication device of claim 25, wherein said first manner is to couple positive terminals to negative terminals, and said second manner is to couple positive terminals to positive terminals and to couple negative terminals to negative terminals.

28. (Original) The communication device of claim 25, wherein reactive elements of said first group and said second group have substantially equivalent inductive impedances and reactive elements of said third group have substantially equivalent capacitive impedances.

29. (Original) The communication device of claim 25, wherein reactive elements of said first group and said second group have substantially equivalent capacitive impedances and reactive elements of said third group have substantially equivalent inductive impedances.